

Compact High-Speed Linear Tracker System



**Developed from the award winning
Trajectory Tracker² system**

Multiple tracking modes

Manual positional adjustment

**Integrated high-speed
camera options**

The Specialised Imaging Tracker^{Lite} is a smaller, lighter system that retains the core functions of the Award winning Tracker² system.

Manual adjustment of three axis rotation and a single input for real-time velocity adjustment contribute to the simplification of the system.

Mounted on heavy, stable tripod, the fully weatherproof mirror/camera housing allows smaller high-speed video cameras with long focal length lenses to be used.

Custom software controls the Tracker and triggering set up, provides calculators for camera fields-of-view and depth of focus for different cameras, lenses and Tracker locations.

FEATURES

- Multiple operating modes allow capture of decelerating, accelerating, user defined velocity profiled projectiles
- Scan ratio (SR) range from 1 to 40 (Optional 1 to 100)
- Typical scanning accuracy of $\pm 0.2^\circ$.
- Gigabit ethernet communications
- Built in camera power, communications and trigger
- No calibration required

OPERATING MODES

Fixed Velocity	Single trigger using known velocity
Velocity	The scan is corrected using the measured velocity from at least 2 of the 3 available detector inputs.
Position	The scan position is corrected from the detector inputs. Known velocity is assumed.
Drag	The scan is corrected using the measured velocity and drag from 3 detector inputs.
Pre-defined profile	Programmable Velocity Vs Time curve. Triggered using single trigger. Used for non-linear projectile trajectories.
Advanced User Functions	Specialised Imaging is prepared to customise modes of operation to user requirements.
Skewed Geometry	Allows non perpendicular operation

OPERATING PARAMETERS

Scan Ratio (SR)	1 to 40, or 1 to 100 (defined as the ratio of projectile velocity/stand-off distance)
Scanning range (Max.)	-50° to +50°
Scanning Distance	≥ 2 x standoff distance (shortest distance between Tracker and line of flight)
Scanning Accuracy	± 0.2° (SR>80 accuracy ± 0.5°)
Calibration	Not required
Projectile Velocity	SR x Standoff distance
Projectile Drag	0 to 100 m/s/m
Acceleration Angle	1° - 5° depending on scan rate (defined as the angle required to accelerate the mirror from rest to full scanning speed)

ENVIRONMENTAL

Storage temperature	-10°C to +74°C
Operating temperature	-5°C to +45°C
Warmup Period	Not Required
Humidity	10 - 90% RH non-condensing
Operational vibration	10G, 10-40Hz Max, any direction
EMC	Meets all UKCA/EU harmonised standards

INPUT / OUTPUT SIGNALS

Detector In	BNC
Number of inputs	3
Trigger In	Make/Break, Positive or Negative edge, Threshold variable to ± 17V 50Ω or 1KΩ termination
Camera Trigger	TTL positive pulse
Communication Interface	Data and command transfer via 1Gbps ethernet cable
Software	Custom software compatible with Microsoft Windows Operating Systems for control and data archiving in various file formats

MECHANICAL

Dimensions mm (w/d/h)	650 x 230 x 310 (without tripod)
Weight	16kg / 35lbs (without camera and lens)
Mount	3/8-16 UNC Female

CONTROL UNIT

System Clock	10MHz quartz crystal controlled
Trigger Jitter	< 1us

MIRROR

Type	Optical flat elliptical surface silvered
Size (HxW) mm	135 x 85

UK (Head Office / Factory)
6 Harvington Park,
Pitstone Green Business Park
Pitstone. LU7 9GX England
Tel +44 (0) 1442 827728

USA
Specialised Imaging Inc.
40935 County Center Dr. Suite D
Temecula, CA 92591, USA
Tel +1 951-296-6406

GERMANY
Hauptstr. 10,
82275 Emmering
Germany
Tel +49 8141 666 89 50

specialised-imaging.com info@specialised-imaging.com



FM 87429



THE QUEEN'S AWARDS
FOR ENTERPRISE:
INNOVATION
2016