

## High resolution multi channel framing camera

**Up to 1 Billion frames per second capture speed**

**50lp/mm system resolution**

**1360 x 1024 pixel, 12-bit sensor resolution**

**Up to 16 discrete intensified optical channels**



The Specialised Imaging SIMX Framing Camera offers up to 16 high resolution images without creating shading, or parallax. Highly accurate timing and fully flexible intensified CCD sensors provide almost infinite control over interframe time, gain and exposure to capture even the most difficult ultra-fast phenomena.

Comprehensive triggering adjustment and a wide range of output signals are controlled using the custom software package which also includes measurement and image enhancement functions.

The SIMX has an optional port for the addition of a high-speed video, or streak camera to allow either simultaneous long duration or ultra high temporal resolution capture. A multi-spectral configuration SIMX camera can provide up to 16 wavelength specific images, or 5 colour and one monochrome image.

### FEATURES

- Fully adjustable interframe time to 1ns
- Fully adjustable exposure down to 3ns
- Gain adjustment up to 10,000X
- Adjustable output triggers
- Nikon lens mount fitting
- Ethernet communications
- Multi-Spectral configuration camera option

## MODELS

	<b>SIMX4</b>	<b>SIMX8</b>	Large body models shown		
			<b>SIMX10</b>	<b>SIMX12</b>	<b>SIMX16</b>
Number of Channels	4	8	10	12	16
Number of images	4	8	10	12	16

Single and multiple channel upgrades are available up to a maximum of 16 channels.

## OPTICAL

Optics	Single input beam splitting optics Channels can be fitted with individual filters
Lenses	Nikon F-Mount
Internal electro-mechanical iris	f2.8 - f22
Shutter	Electro-mechanical
Distortion	Nominally zero
Channel Registration	Within one pixel after software correction
Intensity Variation	Better than 5% across the image
Auxiliary Optical Channel Interface	Nikon F-mount bayonet (Optional)

## INTENSIFIER / SENSOR

Image Sensor	ICX285AL
Active CCD Pixel	1360 (H) x 1024 (V)
Pixel Size	6.45 µm (H) x 6.45 µm (V)
Digitisation	12 bits
Intensifier	Gen II 18mm High resolution MCP Input window Fused Silica Output window Fibre Optic Photocathode S25, others available on request Phosphor screen P43 Gen III intensifiers available on request
Gain	Variable up to 10,000
System resolution	50 lp/mm

## MECHANICAL

Dimensions in cm (LxWxH)	57.2 x 43.8 x 31.9 (> 8CH, without lens) 57.2 x 23.8 x 31.9 (< 8CH, without lens)
Mount	3/8-16 UNC Female
Weight	30Kg (> 8CH, without lens) 24Kg (< 8CH, without lens)

## TIMING PARAMETERS

System Clock	1GHz quartz crystal controlled
Exposure Mode (each image)	Single exposure or multiple exposures (Max. 8) per channel
Exposure Time	3ns - 10ms in 1ns steps independently variable
Interframe Time	0ns - 20ms in 1ns steps independently variable
Delay to 1st exposure	65ns to 10ms in 1ns steps, independently variable
Flash Outputs	5ns - 1ms in 1ns steps independently variable
Framing rates	up to 1 Billion fps

## INPUT / OUTPUT SIGNALS

Trigger 1	Electrical signal (BNC connector) Threshold variable from ± 25V Positive or Negative polarity, Make/Break 50Ω or 1KΩ termination
Trigger 2	Electrical signal (BNC connector) Threshold variable from ± 25V Positive or Negative polarity, Make/Break 50Ω or 1KΩ termination
Timing Monitor Pulses	Pulse width (min. 3ns) and position user programmable TTL into 50Ω
Flash Trigger Outputs	Pulse width (min. 5ns) and position user programmable TTL into 50Ω
Camera control	Data and command transfer via 100Mbps ethernet cable length 10m (standard), other lengths up to 100m available 100FX fibre optic ethernet link (up to 2Km) - optional
Software	Custom software compatible with Microsoft Windows Operating Systems for camera control, image data archiving in various file formats.
Electrical input	Mains 100-240V AC 50-60Hz

## ENVIRONMENTAL

Storage temperature	-10°C to +50°C
Operating temperature	-5°C to +40°C
Humidity	10 - 90% RH non condensing
Vibration shock	10 - 40 Hz Max. 10g in any direction
EMC	Meets all UKCA/EU harmonised standards

**UK** (Head Office / Factory)  
6 Harvington Park,  
Pitstone Green Business Park  
Pitstone. LU7 9GX England  
**Tel +44 (0) 1442 827728**

**USA**  
Specialised Imaging Inc.  
40935 County Center Dr. Suite D  
Temecula, CA 92591, USA  
**Tel +1 951-296-6406**

**GERMANY**  
Hauptstr. 10,  
82275 Emmering  
Germany  
**Tel +49 8141 666 89 50**



FM87429