

AD-500



Single or multiple head high intensity flash system



- 500J Flash head with 2ms duration**
- Up to four independent flash heads**
- 40s recycle time**
- Standard trigger**

The Specialised Imaging AD500 Flash system offers the flexibility of four controllable high intensity flash light for used in scientific and industrial environments.

CONTROL UNIT

Signal Input	Four independent Channels
Trigger Mode	1. Independently 2. Simultaneous - all four channels triggered via channel 1
Trigger Source	Short Circuit 5-100V positive edge
Input Impedance	50Ω per channel
Mains Input	IEC socket
Input Voltage	90-240V 50-50Hz AC
Dimensions mm	(LxWxH) 220mm x 110mm x 128mm
Weight	3.7kg
EMC	Meets all UKCA/EU harmonised standards

FLASH HEAD

Light Duration (Typ)	2ms measured to 50% of peak output
Stored Charge (max)	500J
Charge Voltage	340V
Light Source	U-Shape Xenon flashtube
Rise Time	50µs
Delay (typ)	30µs
Recycling Time (typ)	40 seconds
Dimensions	(LxDia) 270mm x 170mm
Weight (Kg)	5.25kg
Lamp cable length	2.5m
EMC	Meets all UKCA/EU harmonised standards

UK (Head Office / Factory)
6 Harvington Park,
Pitstone Green Business Park
Pitstone. LU7 9GX England
Tel +44 (0) 1442 827728

USA
Specialised Imaging Inc.
40935 County Center Dr. Suite D
Temecula, CA 92591, USA
Tel +1 951-296-6406

GERMANY
Hauptstr. 10,
82275 Emmering
Germany
Tel +49 8141 666 89 50



FM 87429



specialised-imaging.com info@specialised-imaging.com

MSFH-370



High intensity flash
with dedicated fibre
optic output



The Specialised Imaging MSFH-370 Flash system offers the flexibility of four controllable high intensity flash light for used in scientific and industrial environments. 5mm diameter FO output.

370J Flash head with 750µs duration
Up to four independent flash heads
40s recycle time
Standard trigger

CONTROL UNIT

Signal Input	Four independent Channels
Trigger Mode	1. Independently 2. Simultaneous - all four channels triggered via channel 1
Trigger Source	Short Circuit 5-100V positive edge
Input Impedance	50Ω per channel
Mains Input	IEC socket
Input Voltage	90-240V 50-50Hz AC
Dimensions mm	(LxWxH) 220 x 120 x 90 mm
Weight	4.5 kg
EMC	Meets all UKCA/EU harmonised standards

FLASH HEAD

Light Duration (Typ)	750µs measured to 50% of peak output
Stored Charge (max)	370J
Charge Voltage	340V
Light Source	Linear spark source flashtube
Rise Time	50µs
Delay (typ)	30µs
Recycling Time (typ)	40 seconds
Dimensions	(LxDia) 270 x 170 mm
Weight (Kg)	5.25 kg (without handle, legs, FO mounting)
Lamp cable length	2.5m
EMC	Meets all UKCA/EU harmonised standards

UK (Head Office / Factory)
6 Harvington Park,
Pitstone Green Business Park
Pitstone. LU7 9GX England
Tel +44 (0) 1442 827728

USA
Specialised Imaging Inc.
40935 County Center Dr. Suite D
Temecula, CA 92591, USA
Tel +1 951-296-6406

GERMANY
Hauptstr. 10,
82275 Emmering
Germany
Tel +49 8141 666 89 50



FM 87429



THE QUEEN'S AWARDS
FOR ENTERPRISE:
INNOVATION
2016

specialised-imaging.com info@specialised-imaging.com