





The Specialised Imaging T-Cam Camera offers single high resolution monochrome images.

Comprehensive triggering adjustment and a wide range of output signals are controlled using the custom software package which includes measurement and image enhancement functions.

FEATURES

- ☐ Fully adjustable exposure from 1µs to 10ms
- ☐ Adjustable output triggers
- □ Nikon lens mount fitting
- ☐ Gigabit ethernet communications



High Resolution non-intensified camera



Distortion OPTICAL Nikon F-mount Limited by lens Nominally zero

SENSOR			
	T-Cam 43100	T-Cam 22100	
Image Sensor	KAI11002M	KAI4021M	
Active CCD Pixel	4008 (H) x 2688 (V)	2048 (H) x 2048 (V)	
Pixel Size	9μm (H) x 9μm (V)	7.4 µm (H) x 7.4 µm (V)	
Dynamic Range	12 bits	12 bits	

MECHANICAL	
Dimension mm (w/d/h)	17.8cm x 18.5cm x 19.7cm (7.0″ x 7.3″ x 7.8″) without lenses
Mount	1/4-20 UNC Female (standard tripod)
Weight	6Kg (13.2lbs) without lens.

Trigger 1	Electrical signal (BNC connector) Threshold variable from ± 25V Positive or Negative polarity, Make/Break 50Ω or 1KΩ termination
Trigger 2	Electrical signal (BNC connector) Threshold variable from ± 25V Positive or Negative polarity, Make/Break 50Ω or 1KΩ termination
Flash Trigger Output	Pulse width (min. 10ns) and position user programmable. TTL into 50Ω
Camera Control	Data and command transfer via Gigabit Ethernet. Cable length 10m (standard), other lengths up to 100m available 1000FX fibre optic Ethernet link (up to 2Km) - optional
Software	Custom software compatible with Microsoft Windows Operating Systems for camera control, image data archiving in various file formats.
Electrical input	Mains 100-240V AC 50-60Hz

ENVIRONMENTAL		
orage temperature	-10°C to +50°C	
perating temperature	-5°C to +40°C	
umidity	10—90% RH non condensing	
bration shock	10—40 Hz Max. 10g in any direction	
ЛС	Meets all UKCA/EU harmonised standards	
ЛС	Meets all UKCA/EU harmonis	

UK (Head Office / Factory) 6 Harvington Park, Pitstone Green Business Park Pitstone. LU7 9GX England

Tel +44 (0) 1442 827728

USA

Specialised Imaging Inc. 40935 County Center Dr. Suite D Temecula, CA 92591, USA

Tel +1 951-296-6406

GERMANY

Hauptstr. 10, 82275 Emmering Germany

Tel +49 8141 666 89 50



FM 87429